

Postbus 540 7550 AM Hengelo (Ov) +31(0)74 3490022 www.naumetrics.nl info@naumetrics.nl



## Industrial Microscope Series ZTX 10/20



ZTX-20-C2

## **FEATURES**

- 1. Sharp stereo erect image over a wide field of view.
- 2. 45°inclined and 360°rotatable binocular head with locked-in eyepiece, The left ocular-tube with diopter adjustment ±5dp, The interpupillary distance is between 55-75mm.
- 3. Three kind of 90° rotatable objective for selection:  $1 \times /2 \times , 1 \times /3 \times , 2 \times /4 \times$
- 4. ZTX-10/ZTX-20 series supplied with pillar style stand; ZTX-10-C series supplied with fan base and pillar stand, ZTX-20-W series supplied with arm curved style stand.
- 5. CE approval.
- 6. Power supply 110V/60Hz or 220V/50Hz.
- 7. Each set packed in styrofoam box and in an inner box.Two or Four sets in one outer carton.The outer measurement is ZTX-10/20:85×35×40cm ZTX-20-W:50×37×48cm.
- 8. A wide range of accessories for selection.



Postbus 540 7550 AM Hengelo (Ov) +31(0)74 3490022 www.naumetrics.nl info@naumetrics.nl



	Objective			Auxiliary Objective								
Eyepiece				0.5×		0.75×		1.5×		2.0×		
	Objective	Field of view (mm)	Working Distance	Field of view (mm)	Working Distance	Field of view (mm)	Working Distance	Field of view (mm)	Working Distance	Field of view (mm)	Working Distance	
WF5x	1×	20	109	37.5	120	24	75	14	40	11	25	
	2×	10	99	19	120	12	75	7	40	5.5	25	
	3×	7	84	12.5	120	8	75	4.5	40	3.5	25	
	4×	5	81	19	120	6	75	3.5	40	2.8	25	
WF10×	1×	20	109	37.5	120	25	75	14	40	11	25	
	2×	10	99	19	120	12	75	7	40	5.5	25	
	3×	7	84	12.5	120	8	75	4.5	40	3.5	25	
	4×	5	81	19	120	6	75	3.5	40	3	25	
WF15×	1×	15	109	30	120	18	75	10	40	8	25	
	2×	7.5	99	15	120	9	75	5	40	4	25	
	3×	5	84	9.5	120	6	75	3.5	40	3	25	
	4×	3.8	81	7	120	4.5	75	2.8	40	2	25	
WF20×	1×	10	109	19	120	12	75	7	40	5.5	25	
	2×	5	99	10	120	6	75	3.5	40	2.5	25	
	3×	3.5	84	6.2	120	4	75	2.4	40	2	25	
	4×	2.5	81	4.7	120	3	75	2	40	1.5	25	

## Illumination:

L1:Incident reflected halogen light 12V 10W;Transmitted halogen light 12V 10W,Brightness is adjustable.

L2:Both incident and transmitted light with LED 1W,Brightness is adjustable.

## **SPECIFICATION**

Model	Eyepiece	Objective	Working Stage	Illumination	
ZTX-20-C2	WF10×		Frosted glass	LED illumination	
ZTX-20	WF10×	1x-2x	Frosted glass	Halogen Lamp illumination	
ZTX-10-C1	WF10×	1x-3x	White/black	Natural illumination	
ZTX-10	WF10×	2x-4x	White/black	Natural illumination	

Optional accessories : 0.5×、0.75x、1.5×、2× Auxiliary Objective;WF5×、WF10×、WF15x、WF20× Eyepiece;Ring light、Darkfield Attachment、. Jewel Tweezer